

# **USB Type-C Port Protector**



# **1. General Description**

The FA2214 is a single-chip USB Type-C port protection device that provides 48V Short-to-V<sub>BUS</sub> protection. Since the release of the USB Type-C connector, many products and accessories for USB Type-C have been released that do not meet the USB Type-C specification. One example of this is USB Type-C Power Delivery adaptors that only place 48V on the V<sub>BUS</sub> line. Another concern for USB Type-C is that mechanical twisting and sliding of the connector could short pins due to the close proximity they have in this small connector. This can cause 48V V<sub>BUS</sub> to be shorted to the CC and SBU pins. Also due to the proximity of the pins in the Type-C connector, there is a heightened concern that debris and moisture will cause the 48V V<sub>BUS</sub> pin to be shorted to the CC and SBU pins.

These non-ideal equipment and mechanical events make it necessary for the CC and SBU pins to be 48V tolerant, even though the pins only operate at 5V or lower. The FA2214 enables the CC and SBU pins to be 48V tolerant without interfering with normal operation by providing over-voltage protection on the CC and SBU pins. The device places high voltage FETs in series on the CC and SBU lines. When a voltage above the OVP threshold is detected on these lines, the high voltage switches are opened up, isolating the rest of the system from the high voltage condition present on the connector.

#### **Features**

- 4-Channels of Short-to-V<sub>BUS</sub> Overvoltage Protection (C\_CC1, C\_CC2, C\_SBU1, C\_SBU2)
- 6-Channels of IEC 61000-4-2 ESD Protection (C\_CC1, C\_CC2, C\_SBU1, C\_SBU2, D1, D2)
- 600mA Capable for Passing V<sub>CONN</sub> Power
- CC Dead Battery Resistors Integrated for Handling Dead Battery Use Case
- Halogen Free, RoHS and TSCA Regulations Compliant
- WLCSP25\_2.3mm x 2.3mm Package

## **Ordering Information**

FA2214

Package Type W: WLCSP Packing Code R: Tape & Reel

## **Marking Information**

